

CARLSTAR



Hints and features:

- Lawn tyre for all kinds of devices for professional lawn and landscape maintenance.
- Wide range of applications from zeroturn rotary mowers to utility vehicles.
- Tread design effectively protects green spaces.
- High tread depth guarantees longevity.

IMPLEMENT TYRE (FOR TRAILERS) 15 X 6.00 - 6"

4 PR, TL, TURF TRAC, 5753191 CARLISLE

Product-No.: 12500154

Technical Information:

Product No.	12500154
Tyre Size	15 x 6.00 - 6
R/D	Diagonaal
TL/TT	TL
LI / SI	61 A4
PR	4
Tread	Turf Trac R/S
Manufacturer	Carlstar
Recom. Rim	4.50
Permissible rim	4.50A
Width mm	160
Outer diameter mm	366
Static radius mm	163
Rolling circumference mm	1087
Payload in kg at kph (1)	257 / 20
Inflation pressure bar	2,07
Weight kg	2,7
Stud height mm	4,1
Certified	ECE 106
Nominal width [inch]	6.00
Nominal diameter [inch]	15
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.