





Hints and features:

- The BKT AT 316 is a small agricultural tyre suitable for compact tractors in municipal work and maintenance
- Its tread pattern provides excellent traction and outstanding soil protection at the same time

ALL TERRAIN VEHICLE TYRE 24 X 12.00 - 12 4 PR, 99 A3, TL, AT-316 ,AS, BKT NOT E-MARK

Product-No.: 15710230

Technical Information:

Product No.	15710230
Tyre Size	24 x 12 - 12
R/D	Diagonaal
TL/TT	TL
LI/SI	95 A6
PR	4
Tread	AT 316
Manufacturer	BKT
Recom. Rim	10.50I-55, 10.50I-70, 10.50I-90
Permissible rim	10.5
Width mm	315
Outer diameter mm	610
Static radius mm	271
Rolling circumference mm	1769
Payload in kg at kph (1)	690 / 30
Inflation pressure bar	1,40
Weight kg	10,44
Stud height mm	12,0
Certified	ECE 106
Nominal width [inch]	12
Nominal diameter [inch]	24

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.