





Hints and features:

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Band 520 / 70 R 34, Agrimax RT 765 148 D, TL BKT

Product-No.: 15726821

## **Technical Information:**

Product No.	15726821
Tyre Size	520 / 70 R 34
R/D	Radiaal
TL/TT	TL
LI / SI	148 D
Tread	Agrimax RT 765
Manufacturer	BKT
Recom. Rim	W16L
Permissible rim	W15L, W18L
Width mm	516
Outer diameter mm	1640
Static radius mm	739
Rolling circumference mm	4927
Payload in kg at kph (1)	3150 / 65
Inflation pressure bar	1,60
Weight kg	151,39
Stud width mm	43
Stud height mm	54,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	520
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.