





Hints and features:

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.

Band 320 / 65 R 16, AC 65 120 A8 / 117 D, TL Mitas

Product-No.: 10927540

Technical Information:

Product No.	10927540
Tyre Size	320 / 65 R 16
R/D	Radiaal
TL / TT	TL
LI/SI	120 A8 / 117 D
Tread	AC 65
Manufacturer	Mitas
Recom. Rim	10
Permissible rim	9, 11
Width mm	316
Outer diameter mm	844
Static radius mm	373
Rolling circumference mm	2497
Payload in kg at kph (1)	1400 / 40
Payload in kg at kph (2)	1285 / 65
Inflation pressure bar	2,40
Weight kg	36,5
Certified	niet vereist
Nominal width [mm]	320
Aspect ratio	65
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.