Bohnenkamp Moving Professionals

Kleber



Hints and features:

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Band 280 / 70 R 16, Fitker 112 A8 / 109 B, TL Kleber

Product-No.: 12426005

Technical Information:

Product No.	12426005
Tyre Size	280 / 70 R 16
R / D	Radiaal
TL / TT	TL
LI / SI	112 A8 / 109 B
Tread	Fitker
Manufacturer	Kleber
Recom. Rim	W9
Permissible rim	W8L, W8, W10L
Width mm	263
Outer diameter mm	799
Static radius mm	358
Rolling circumference mm	2373
Payload in kg at kph (1)	1120 / 40
Payload in kg at kph (2)	1030 / 50
Inflation pressure bar	2,40
Weight kg	24
Tyre content 75% litre	50
Stud height mm	29,0
Number of studs	16x2
Certified	niet vereist
Nominal width [mm]	280
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.