





Hints and features:

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.

Band 215 / 75 R 17.5, SDR1 14 PR, 126 / 124 M, TL, 3PMSF HA, Sailun

Product-No.: 11066112

Technical Information:

Product No.	11066112
Tyre Size	215 / 75 R 17.5
R/D	Radiaal
TL/TT	TL
LI/SI	126 / 124 M
PR	14
Tread	SDR1
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	6.00
Permissible rim	6.75
Width mm	211
Outer diameter mm	767
Rolling circumference mm	2260
Payload in kg at kph (1)	1700 / 130
Inflation pressure bar	7,00
Weight kg	29,58
Rolling resistance	E
Wet grip	В
Rolling noise DB	73
Rolling noise level	Α
Stud height mm	15,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	215
Aspect ratio	75

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.