





Hints and features:

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.

Band 215 / 75 R 17.5, SDR1 16 PR, 128 / 126 M, TL, 3PMSF HA, Sailun

Product-No.: 11066108

Technical Information:

Product No.	11066108		
Tyre Size	215 / 75 R 17.5		
R/D	Radiaal		
TL / TT	TL		
LI/SI	128 / 126 M		
PR	16		
Tread	SDR1		
Manufacturer	Sailun		
Specification	3PMSF		
Recom. Rim	6.00		
Permissible rim	6.75		
Width mm	211		
Outer diameter mm	767		
Static radius mm	359.31		
Rolling circumference mm	2339		
Payload in kg at kph (1)	1800 / 130		
Inflation pressure bar	7,50		
Weight kg	29,03		
Rolling resistance	E		
Wet grip	В		
Rolling noise DB	73		
Rolling noise level	A		
Stud height mm	15,0		
Certified	ECE 117, ECE 54		
M+S	M+S		
3PMSF	3PMSF		
Nominal width [mm]	215		
Aspect ratio	75		
Tread symmetry	symmetrisch		

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Benelux B.V. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.