



Band 295 / 60 R 22.5, SFR1+  
18 PR, 150 / 147 L, TL, 3PMSF  
Sailun

**Product-No.: 10002369**



**Leider keine Abbildung!**

#### Hints and features:

- The Sailun SFR1 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption
- The wide tread enables slow and even wear and good handling

#### Technical Information:

Product No.	10002369
Tyre Size	295 / 60 R 22.5
R / D	Radiaal
TL / TT	TL
LI / SI	150 / 147 L
PR	18
Tread	SFR1+
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	295
Outer diameter mm	926
Static radius mm	435
Rolling circumference mm	2806
Payload in kg at kph (1)	3350 / 120
Inflation pressure bar	9,00
Weight kg	49,21
Rolling resistance	C
Wet grip	B
Rolling noise DB	71
Rolling noise level	A
Stud height mm	14,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	295
Aspect ratio	60
Tread symmetry	symmetrisch

